

ELASTO COLOR ANTISLIP

Description:

Elasto Color Antislip is based on non-toxic two component Product . This two packages and is a high build and heavy duty floor Antiskid coating. The product comes with a Filler for purpose of antiskid property in product. It has excellent resistance to cathodic protections. Excellent adhesion to blasted steel surface, Steel ,concrete Surface.

Recommended Use:

- Driveways
- Car parks
- Walkways
- Wet areas
- Staircases
- Hospitals
- Recreation areas
- Kindergartens
- Kitchens



Physical Properties:

Colour: Clear/ wide colours

Vehicle type: Non-toxic resin and hardener

Pigmentation: Titanium dioxide for white, carbon black for black

Mixing ratio: Base (Part 1) : Hardener (Part 2)
4 : 1 (by volume)

Solid content: $\geq 80\%$

Density (kg / litre): 1.27 ~ 1.30 mixed paint

Viscosity: 85 ~ 90 ku

After mixing viscosity: 65 ~ 70 ku

Drying time at

($27 \pm 2^\circ\text{C}$ & RH : $80 \pm 5\%$): Surface dry : ≤ 4 hrs

Hard dry : 16 ~ 24 hrs

Dry film thickness: 100 microns per coat

Recoat interval: 24 hrs (minimum), 48 (maximum)

Theoretical coverage: $5 \text{ m}^2 / \text{litre}$

Chemical resistance:

High resistance to crude and heavy oils, aliphatic hydrocarbon solvent, water, sea water and many chemicals

Packing weight: 20 litres set, 5 litres set

Customers are advised to undertake their own assessment to determine suitability of a product for the particular use intended. Due to the performance of any product being subject

to a wide variety of field and surface conditions we are unable to assume liability for any loss, consequential or otherwise that may arise from the use of our products.

SOLUTIONS FOR CONSTRUCTION

Artsdesign 200 Jalan Sultan,04-22 Textile centre Singapore:199018 PH: 65755420, 91548970 elastic.sg@gmail.com